

Specification	Order-No.	Product detail
<p>Lifting device To simplify the process of lifting the pump in and out of drums and containers.</p>	0155-154	
<p>Hose connection Hose connector with wing nut for connecting the hoses to the pump tube or nozzle.</p> <p>Material: PP Nominal diameter: DN 38</p>	0180-161	
<p>Reducing sleeve G 1 1/2 inner thread to G 1 1/4 outer thread for connection of a flow meter</p> <p>Reducing sleeve G 1 1/2 outer thread to G 1 1/4 inner thread for hose diameter DN 38 when using a flow meter</p>	0180-167 0180-169	
<p>Foot strainer Keeps impurities away from the rotating parts.</p> <p>Material: PP</p>	0180-174	
<p>Acid proof coating In aggressive atmosphere the three phase motor should be protected by a special acid proof coating. If customer requires, a special varnish is possible.</p> <p>Acid proof coating</p>	0006-516	
<p>PVC hose Fabric reinforced PVC hose for aggressive, non-flammable liquids.</p> <p>Operating pressure: max. 6 bar Temperature of medium: 0 up to +60 °C Nominal diameter: DN 38 (1 1/2") Weight: 0.84 kg/m</p>	0374-431	

Hoses, hose clamps and hose connections see pages 83-87