Lutz Pump Sets

0.1 Pump Set B1 Battery (polypropylene)

For thin-bodied fluids

such as battery acid, ammonia water, photographic developer/-fixer, glycols, phosphoric acid, hydrochloric acid and hydrogen peroxide.

For removing small quantities from hobbocks, canisters and drums.

• Motor B1 Battery,

70 Watt internally ventilated

Density (kg/dm³)	Viscosity (mPas)	Delivery rate (I/min.)	Delivery head (m wc)	
1.3	200	20	6	

Max. temperature of medium 40 $^{\circ}\text{C}$

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil.





For emptying canisters and drums	Pump B1 Battery PP 25-L SL		Set B1 Battery PP 25-L SL		Set B1 Battery PP 25-L SL with flow meter TR90-PP			
Motor B1 Battery	~			✓			~	
Flow meter TR90-PP	-			-			~	
Pump tube PP 25-L-SL	~			~			~	
1,5 m PVC hose 3/4"	-			✓			✓	
Hose connectors 3/4"	~			✓			✓	
Hose clamps	-			✓			✓	
Lutz nozzle with suspension hook	-			✓		✓		
Immersion depth	500 mm	700 mm	1000 mm	500 mm	700 mm	1000 mm	1000 mm	
Order No.	0207-112	0207-113	0207-114	0207-090	0207-091	0207-092	0207-093	
Battery 10,8 V	0332-027							
Battery charger	0335-336							