

# Lutz Pump Sets

## 1 Pump Set Lutz B2 Vario (polypropylene)

### For thin-bodied fluids

such as battery acid, ammonia solution, photographic developer/-fixer, glycols, phosphoric acid, hydrochloric acid and hydrogen peroxide.

For filling small quantities from hobbcocks, canisters and drums.

- **Motor Lutz B2 Vario,**  
200 W internally ventilated

Density (kg/dm <sup>3</sup> )	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1.3	300	75 (22)	7

Max. temperature of medium 50 °C

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil. When using a nozzle the delivery rate is reduced to approximate values (see brackets).



### Pump Set Lutz B2 Vario

for thin-bodied fluids



with shaft HC  
(Hastelloy C)



For emptying canisters and drums	Pump Lutz B2 Vario			Set Lutz B2 Vario		
	500 mm	700 mm	1000 mm	500 mm	700 mm	1000 mm
Motor B2 Vario		✓			✓	
Pump tube PP-SL 32		✓			✓	
1,5 m PVC spiral hose 3/4"		-			✓	
Hose connectors PP 3/4"		✓			✓	
Hose clamps		-			✓	
Lutz nozzle		-			✓	
Wall bracket		-			✓	
Immersion depth	500 mm	700 mm	1000 mm	500 mm	700 mm	1000 mm
Order No.	0201-500	0201-501	0201-502	0205-020	0205-021	0205-022