More time for the essential things

Pump Set "Mineral Oil Products" (aluminium) 6

For light viscous mineral oil products

such as diesel, fuel oil, hydraulic oil, machinery oil and motor oil.

- Motor MI-4, 500 W internally ventilated or optionally with
- Compressed air motor MD2xL, 1000 W / 6 bar with stop valve and nipple

Motor MI-4

Density	Viscosity	Delivery rate	Delivery head		
(kg/dm ³)	(mPas)	(I/min.)	(m wc)		
1.4	500	87 (50)			

Motor MD2xL

Density	Viscosity	Delivery rate	Delivery head
(kg/dm ³)	(mPas)	(I/min.)	(m wc)
2,8	1000	116 (65)	36

Max. temperature of medium 100 °C

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil. When using a nozzle the delivery rate is reduced to approximate values (see brackets).





For emptying drums and containers		Pump with motor MI-4		Pump with motor MD2xL		Set with motor MI-4		Set with motor MD2xL	
Pump tube Alu 41-L-SL	×	✓ - - - - -		\checkmark		 Image: A second s		\checkmark	
2 m PVC spiral hose 1"	-			_	\checkmark		\checkmark		
Drum adapter PP	-			- V V V		\checkmark		\checkmark	
Hose connectors Alu 1"	×					1	 Image: A second s		
Hose clamps	-			-		\checkmark		\checkmark	
Nozzle Alu	-			-		 Image: A second s		\checkmark	
Immersion depth	1000 mm	1200 mm	1000 mm	1200 mm	1000 mm	1200 mm	1000 mm	1200 mm	
Order No.	0205-305	0205-306	0205-325	0205-326	0205-301	0205-302	0205-321	0205-322	

(For high viscous oils suitable Eccentric Screw Pumps are available, see separate leaflet)